

Men's shoe with lace fastening. , design A, class I.



STANDARDS: CE CERTIFIED, Directive 89/686/CEE, Regulation 2016/425. Category I. SRC (anti-slip on tiles and water with detergent as a lubricant + Anti-slip on steel and glycerin as a lubricant), EN-ISO-20347:2012 standard.



Available colour: ● black

Sizes:
39 - 46

- Ergonomic footwear.
- Pieces cut using dies by size.
- Upper pieces sewn together.
- Assembly: Upper is stitched to the bottom by Strobel stitch, followed by shaping and assembly.
- Fixed to the sole using direct injection into the upper.
- Padded insole in heel and other pressure areas to provide relief.

Components	Material	Properties/characteristics
UPPER	<ul style="list-style-type: none"> • cloth 	<ul style="list-style-type: none"> • Resistant to tear. • Resistant to traction. • High breathability and absorbency. • Padded ankle. • Lace fastening.
LINING	<ul style="list-style-type: none"> • Microfiber lined with foam 	<ul style="list-style-type: none"> • Antibacterial. • Breathable. • Resistant to abrasion.
COUNTER	<ul style="list-style-type: none"> • Non-woven fabric soaked with resin 	<ul style="list-style-type: none"> • Closed heel. • Rear hold and reinforcement.
INSOLE	<ul style="list-style-type: none"> • Microfiber-coated polyurethane foam 	<ul style="list-style-type: none"> • Removable. • Breathable. • Antibacterial. • Padded. • High comfort.
SOLE	<ul style="list-style-type: none"> • Expanded polyurethane injected into the upper 	<ul style="list-style-type: none"> • Ultralight and flexible. • Non-slip. • Resistant to hydrocarbons. • Thermal insulation. • Low wear and high water-tightness. • Energy absorbent heel.

SCOPE OF USE:

Footwear for the hospitality industry, waiters, spas, drivers, clinics, pharmacies, petrol stations and everyday comfort.